



DECUS

PROGRAM LIBRARY

DECUS NO.	8-474
TITLE	EXIT PS/8
AUTHOR	Edward Steinfeld Submitted by: Karen Seefeldt
COMPANY	Digital Equipment Corporation Pittsburgh, Pennsylvania
DATE	November 11, 1971
SOURCE LANGUAGE	PAL-8

Although this program has been tested by the contributor, no warranty, express or implied, is made by the contributor, Digital Equipment Computer Users Society or Digital Equipment Corporation as to the accuracy or functioning of the program or related program material, and no responsibility is assumed by these parties in connection therewith.

EXIT PS/8

DECUS Program Library Write-up

DECUS NO. 8-474

ABSTRACT

The EXIT program is used to exit from the PS/8 programming system. EXIT will determine what the system device is and load in the proper bootstrap. The program will also load a binary loader into field one and rewind all DECtapes.

All PS/8 bootstraps are loaded so they start at $\$7600$.

The binary loader starts at 17777 and determines if input is from a high speed reader or teletype. (Do not have tape in both readers and you do not have to set bit zero of the switch register to zero for the high speed reader.)

If the system device is a TD8E unit zero is rewound and the binary loader is loaded. No bootstrap is loaded.

To bootstrap back PS/8: Load address $\$7600$ and start

DECtape Directory

EXIT .BN	3	11/10/71	BINARY
EXIT .SV	5	11/10/71	CORE IMAGE
MESAGE	2		INSTRUCTIONS
EXIT	10	11/10/71	SOURCE
EXIT .LS	29	11/10/71	PAL LISTING
EXIT .CF	41	11/10/71	CREF LISTING
640 FREE BLOCKS			

*

